



Solenoid coil, MSFW-230-50/60

URL: <https://www.sxplc.com/solenoid-coil-msfw-230-50-60>

Product data sheet

- | | |
|---|--|
| • Mounting position | optional |
| • Switching position indicator | no |
| • Min. pick-up time | 10 ms |
| • Duty cycle | 100% |
| • Power factor (cos phi) | 0.7 |
| • Characteristic coil data | 230 V AC: 50/60 Hz, pick-up power 9.0 VA, holding power 7.0 VA |
| • Permissible frequency fluctuations | +/- 5% |
| • Permissible voltage fluctuations | +/- 10 % |
| • CE mark (see declaration of conformity) | To EU Low Voltage Directive |
| • CE marking (see declaration of conformity) | To UK regulations for electrical equipment |
| • LABS (PWIS) conformity | VDMA24364-C1-L |
| • Degree of protection | IP65 |

- **Ambient temperature**-5 °C ... 40 °C
- **Max. tightening torque for socket**0.4 Nm
- **Product weight**55 g
- **Electrical connection**3-pin Plug pins with connection pattern to Festo standard for MSSD-F
- **Type of mounting**Via knurled nut
- **Note on materials**RoHS-compliant
- **Material solenoid coil**Duroplast Copper Steel
- **Material winding**Copper

