Automatic Float Drain: M12.FD.0001

URL:https://www.sxplc.com/automatic-float-drain-m12-fd-0001

Product data sheet

Dimensions
Width (In.) 0.95 in
Base Dia. (In.) 0.95 in
Height (In.) 3.23 in
Details
Function Clamps and Tie Rod Kits Connect Multiple Filter Housings, Incident Motor Used to Indicate
Premature High Differential Pressure, Mounting Brackets Provide Support to Filters Installed in Flexible
Piping Systems or OEM Equipments
For Use With Model Number 010-055
Item Automatic Float Drain
Connection Female

1/3

Application Compressed Air Filters
Provides Mounting Brackets Provide Support to Filters Installed in Flexible Piping Systems or OEM Equipment
Replaces PD15NO
For Use On OIL-X Compressed Air Filter, OIL-X EVOLUTION Compressed Air Filter
Fitting 1/4 in to 4 in Models
Adjustment Range (PSI) 22 to 232 psi
Max. Working Pressure (PSI) 232 psi
Max. Pressure (PSI) 232 psi
Includes Clamps, Incident Monitors, Mounting Bracket Kits, O Ring Kits, Replacement Drains, Tie Rod Kits
Type Automatic Float Drain
Design Type Automatic Float Drain
For Use on Filter Parker OIL-X Models 010-055
Fits OIL-X Compressed Air Filter, OIL-X EVOLUTION Compressed Air Filter

