



cylinder ADVU-25-40-P-A-S2

URL:<https://www.sxplc.com/cylinder-advu-25-40-p-a-s2>

Product data sheet

stroke

1 mm 200 mm

Piston diameter

25 mm

buffer

Elastic buffer rings/pads at both ends

Installation location

Optional

Working mode

Double action

End of piston rod

Internal thread

Structural characteristics

Cylinder diameter

piston rod

position detection

By proximity switch

symbol

00991219

Derived type

Double end piston rod

working pressure

0.12 Mpa 1 Mpa

working pressure

1.2 bar 10 bar

working pressure

17.4 psi 145 psi

Working medium

Compressed air, in accordance with ISO 8573-1:2010 [7:4:4]

Description of Work and Pilot Media

Can work with lubricating medium (must continue to work with lubricating medium thereafter)

Corrosion resistance grade CRC

2- Moderate corrosion resistance

Paint Wetting Defect Substance (PWIS) Compliance

VDMA24364-B1/B2-L

ambient temperature

-20 ° C 80 ° C

Impact energy at the end position

0.1 J

Theoretical force value at 6 bar, return stroke

247 N

Theoretical force value at 6 bar, forward travel

247 N

Installation method

Either:

With through-hole

With attachments

Pneumatic interface

M5

Ring screw material

Galvanized steel

Lid material

Refined aluminum alloy

Dynamic sealing material

NBR

TPE-U (PU)

Material of piston rod

High alloy stainless steel

Cylinder material

Refined aluminum alloy

