



Motor □ MHMD082G1U

URL: <https://www.sxplc.com/motor-mhmd082g1u>

Product data sheet

Item		Specifications
Part Number	MHMD082G1U	
Details	High inertia, Lead wire type, IP65	
Family Name	MINAS A5	
Series	MHMD Series	
Type	High inertia	
Protection class	IP65	
About Enclosure	Except rotating portion of output shaft and leadwire end.	
Environmental Conditions	For more details, please refer to the instruction manual.	
Flange sq. dimension	80 mm sq.	
Flange sq. dimension (Unit:mm)	80	
Motor lead-out configuration	Lead wire	
Motor encoder connector	Lead wire	
Power supply capacity (kVA)	1.3	
Voltage specifications (V)	200	
Rated output (W)	750	
Rated current (A (rms))	4.0	
Holding brake	without	
Mass (kg)	2.5	

Oil seal	with
Shaft	Key-way, center tap
Rated torque (N ? m)	2.4
Momentary Max. peak torque (N ? m)	7.1
Max. current (A (o-p))	17.0
Regenerative brake frequency (times/min)	Without option :No limit With option :No limit Option (External regenerative resistor) Part No. : DV0P4283
About regenerative brake frequency	Please refer to the details of [Motor Specification Description] , Note: 1, and 2.
Rated rotational speed (r/min)	3000
Rated rotational Max. speed (r/min)	4500
Moment of inertia of rotor ($\times 10^{-4}$ kg ? m ²)	1.51
Recommended moment of inertia ratio of the load and the rotor	20 times or less
About recommended moment of inertia ratio of the load and the rotor	Please refer to the details of [Motor Specification Description] ,Note: 3.
Rotary encoder: specifications	20-bit Incremental system
Rotary encoder: Resolution	1048576

