## 378 FC Non-Contact Voltage Truerms AC/DC Clamp Meter with iFlex

URL:https://www.sxplc.com/378-fc-non-contact-voltage-true-rms-ac-dc-clamp-meter-with-iflex

## **Product data sheet**

Fluke 378 FC Non-Contact Voltage True-rms AC/DC Clamp Meter with iFlex

Model#: FLUKE-378 FC Part#: 5111812 UPC#: 0 95969 91661 5

Key features

Measure voltage and current with your clamp jaw

Faster, safer testing - all without touching a live wire - using FieldSense™ technology

Power quality indicator shows whether equipment or power line is faulty

Complete 3-phase voltage and current tests in 3 quick steps

1/3

Product overview: Fluke 378 FC Non-Contact Voltage True-rms AC/DC Clamp Meter with iFlex

Voltage and current measurements with FieldSense™ technology

The Fluke 378 FC true-rms clamp meter uses FieldSense™ technology to make testing faster and safer, all without contacting a live conductor. You get accurate voltage and current measurements through the clamp jaw. Simply clip the black test lead to any electrical ground, put the clamp jaw around the conductor and see reliable, accurate voltage and current values on the display.

Power quality indicator shows whether a problem is in the equipment or the power line

The 378 FC clamp meter includes a unique PQ function that senses power quality issues automatically. When making FieldSense measurements, the 378 FC will detect and display power quality issues, relating to current, voltage, power factor or any combination of the three. Now you can quickly determine if an upstream supply problem exists, or if there is a downstream equipment problem.

Complete 3-phase measurements in quick, easy steps

Complete 3-phase voltage and current tests in 3 easy steps

Full set of phase-to-ground and phase-to-phase values calculated and shown on the meter

Values are also displayed on your smart phone and saved to the cloud via Fluke Connect software

Phase rotation auto-calculated and shown on the Fluke Connect software

No more hand-written notes or complicated math.

2/3

Measure extremely high current with iFlex® probe

The included iFlex flexible current probe lets you measure ac current as high as 2500 A. Crowded wiring cabinets and large conductors are easily measured with the iFlex probe.

Easy to see, easy to use with included tools

Your job will get easier when you use the 378 FC clamp meter. The display turns green when a stable FieldSense measurement is detected. Visual Continuity also provides a bright green screen for easy detection of continuity in noisy work areas.

Record, analyze, share results with Fluke Connect® software

With Fluke Connect software you can remotely log, trend and monitor measurements to pinpoint intermittent faults. Fluke Connect also allows you to gather data as the basis for a preventive maintenance program.



3/3