



Shut off valve□HE-D-MAXI

URL:<https://www.sxplc.com/shut-off-valve-he-d-maxi>

Product data sheet

- | | |
|---|---|
| • Structural design | Piston gate valve |
| • Actuation type | Manual |
| • Sealing principle | Soft |
| • Exhaust air function | Without flow control option |
| • Manual override | None |
| • Symbol | 00995571 |
| • Valve function | 3/2, bistable |
| • Operating pressure | 0 MPa ... 1.6 MPa |
| • Operating pressure | 0 bar ... 16 bar |
| • Operating medium | Compressed air as per ISO 8573-1:2010 [7:4:4]
Inert gas |
| • Information on operating and pilot media | Operation with oil
lubrication possible (required for further use) |
| • Corrosion resistance class (CRC) | 2 - Moderate corrosion stress |
| • Note on materials | RoHS-compliant |

- **LABS (PWIS) conformity**VDMA24364-B1/B2-L
- **Temperature of medium**-10 °C ... 60 °C
- **Ambient temperature**-10 °C ... 60 °C
- **Type of mounting**Line installation With accessories
- **Mounting position**Any
- **Flow direction**Non-reversible
- **Product weight**796 g
- **Pneumatic connection**3G3/8
- **Air quality class at the output**Compressed air as per ISO 8573-1:2010 [7:4:4] Inert gas
- **Seals material**NBR
- **Housing material**Die-cast aluminum

