



Plug QSC-8H 153269

URL:<https://www.sxplc.com/plug-qsc-8h-153269>

Product data sheet

Specifications

standard

Installation location

Optional

Design

Plug

Package specifications

ten

Complete temperature range under working pressure

-0.095 Mpa ... 0.6 Mpa

Working pressure complete temperature range

-0.95 bar ... 6 bar

Complete temperature range under working pressure

-13.775 psi ... 87 psi

Working pressure dependent on temperature

-0.095 Mpa ... 1.4 Mpa

Working pressure dependent on temperature

-0.95 bar ... 14 bar

Working pressure dependent on temperature

-13.775 psi ... 203 psi

Working medium

Compressed air, in accordance with ISO 8573-1:2010 [7: -: -]

The moisture content complies with the manufacturer's declaration of conformity on www.festo.com

Description of Work and Pilot Media

Working with lubricating media available

Corrosion resistance grade CRC

1- Low corrosion resistance

Paint Wetting Defect Substance (PWIS) Compliance

VDMA24364-B1/B2-L

Cleanroom level

Static installed components cannot be meaningfully evaluated according to ISO 14644-1

ambient temperature

-10 °C ... 80 °C

Product weight

1 g

Air interface, air port 1

Insert type shaft sleeve Ø 8 mm

Material Description

RoHS compliance

Shell material

PBT

