
URL:<https://www.sxplc.com/plug-acp6034bc>

Product data sheet

Features

- Interlinked and interconnected with a broad range of assessment and diagnostic tools, the platform allows you to track and monitor the performance of your students in real time. The platform also provides a comprehensive set of data and analytics that can be used to identify areas of improvement and to tailor your instruction to meet the needs of your students. The platform is designed to be easy to use and to integrate with your existing workflow. The platform is also designed to be scalable and to support a wide range of devices and operating systems. The platform is also designed to be secure and to protect your data. The platform is also designed to be flexible and to support a wide range of assessment and diagnostic tools. The platform is also designed to be easy to integrate with your existing workflow. The platform is also designed to be scalable and to support a wide range of devices and operating systems. The platform is also designed to be secure and to protect your data. The platform is also designed to be flexible and to support a wide range of assessment and diagnostic tools.

• Specifications

Hazardous Area Classification

Class I, Division 1 and 2, Groups B, C, D; Class II, Division 1 and 2, Groups F, G; Class III; NEMA 3, 3R, 4, 4X, 7CD, 9FG

Amperage

30, 60 or 100

Voltage

120 Vac, 240 Vac, 480 Vac or 600 Vac

Number of Poles

4

Number of Wires

3

Plug Cable Diameter

30 Amp: 0.500 to 1.125#8221;, 60 Amp: 0.500 to 1.375#8221;,
100 Amp: 0.875#8221; to 1.906#8221;

Wire Range

30 Amp: #10-#8, 60 Amp: #6-#4, 100 Amp: #2-1/0

Mounting Box Entries

Feed-Thru

Materials and Finishes

Receptacles, mounting box, covers and plug housings are copperfree (4/10 of 1% max.) aluminum with epoxy powder coat. Insulating blocks are fiber glass reinforced polyester.

