



SAFETY LOCK-SZ 2416.000

URL:https://www.sxplc.com/safety-lock-sz-2416-000

Product data sheet

Product description

Article number:

SZ 2416.000

Product description

Fitted to doors, to protect against contact with live electrical equipment while the master switch is ON.

Function principle

Locks the door when the main switch is ON.

Mains power (voltage) is only enabled whilst the door is
closed.
Monitoring of the lock magnet via an additional closing
contact.
Supply includes
Lock
Actuator
Angle bracket
Fasteners
Mounting tip
In the case of double-door enclosures, the door-operated
switch is required for the overlapping door to indicate
"enclosure door closed"
Suitable for

Enclosure type: VX
Enclosure type: VX SE
Enclosure type: TS
Rated power Pel
At 50 Hz: 11 VA
At 60 Hz: 11 VA
Rated operating voltage
230 V
Rated insulation voltage
400 V AC
Rated impulse withstand voltage, phase to phase
4000 V AC

Packaging unit
1 pc(s).
Weight/packaging unit
0.74 kg
(1.6 lb.)
Customs tariff number
83015000
EAN
4028177022652
ETIM 7.0
EC002626
ECLASS 8.0

27189266

Product description

SZ Safety lock, 230 V AC



5/5