



Photoelectric Sensor, E3FA-DP12 2M

URL:https://www.sxplc.com/photoelectric-sensor-e3fa-dp12-2m

Product data sheet

Shape	Cylinder type
Sensing method	Diffuse-reflective

1/8

Sensing distance	White paper 300 x 300 mm: 300 mm
Spot size	40 x 50 mm (sensing distance: 300 mm)
Differential distance	20% max.
Light source	Red LED (624 nm)

Power supply voltage	10 to 30 VDC±10% ripple (p-p) 10% included
Current consumption	25 mA max.
Control output	PNP open collector 30 VDC max. 100 mA max. Residual voltage: 3 V max.

Protective circuit Output short-circuit protection, Output reverse protection, Power supply reverse polarity protection.	
Response time Operate or reset: 0.5 ms max.	

Sensitivity setting	Single-turn adjustment
Ambient illuminance	Incandescent lamp: 3,000 lx max. Sunlight: 10,000 lx max.
Ambient temperature range (Operating)	-25 to 55 ? (with no freezing or condensation)
Ambient temperature range (Storage)	-40 to 70 ? (with no freezing or condensation)

Ambient humidity range (Operating)	35 to 85 % (with no condensation)
Ambient humidity range (Strage)	35 to 95 % (with no condensation)
Insulation resistance	20 M? min. (500 VDC megger)

Dielectric strength	1000 VAC 50/60 Hz 1 min
Vibration resistance	Destruction: 10 to 55 Hz, 1.5 mm double amplitude each in X, Y, and Z directions for 2 h
Shock resistance	Destruction: 500 m/s ² 3 times each in X, Y and Z directions
Degree of protection	IEC: IP67

	DIN40050-9: IP69K
Connection method	Pre-wired models (Cable length 2 m)

