## Photoelectric Sensors E3FA-TP11 2M

URL:https://www.sxplc.com/photoelectric-sensors-e3fa-tp11-2m

## **Product data sheet**

Shape	Cylinder type
Sensing method	Through-beam type

Sensing distance	20 m
Standard sensing object	Opaque: 7 mm dia. min.
Directional angle	2 ° min.
Light source	Red LED (624 nm)

Power supply voltage	10 to 30 VDC±10% ripple (p-p) 10% included
Current consumption	Emitter: 25 mA max. Receiver: 15 mA max.
Control output	PNP open collector  30 VDC max.  100 mA max.  Residual voltage: 3 V max.

Operation mode	Light-ON/Dark-ON selectable
Protective circuit	Output short-circuit protection, Output reverse polarity protection, Power supply reverse polarity protection
Response time	Operate or reset: 0.5 ms max.

Sensitivity setting	Single-turn adjustment
Ambient illuminance	Incandescent lamp: 3,000 lx max.  Sunlight: 10,000 lx max.
Ambient temperature range (Operating)	-25 to 55 ? (with no freezing or condensation)
Ambient temperature range (Storage)	-40 to 70 ? (with no freezing or condensation)

Ambient humidity range (Operating)	35 to 85 % (with no condensation)
Ambient humidity range (Strage)	35 to 95 % (with no condensation)
Insulation resistance	20 M? min. (500 VDC megger)

Dielectric strength	1000 VAC 50/60 Hz 1 min
Vibration resistance	Destruction: 10 to 55 Hz, 1.5 mm double amplitude each in X, Y, and Z directions for 2 h
Shock resistance	Destruction: 500 m/s <sup>2</sup> 3 times each in X, Y and Z directions
Degree of protection	IEC: IP67

	DIN40050-9: IP69K
Connection method	Pre-wired models (Cable length 2 m)
Indicator	Operation indicator (orange), Stability indicator (green),  Power indicator (green)
Weight	Package: Approx. 110 g

Accessories	Instruction sheet, M18 nuts
Material	Case: ABS  Lens: Methacrylate resin (PMMA)  Display: Methacrylate resin (PMMA)  Adjustment: POM  Nut: POM

