



Contactor LADN31

URL:https://www.sxplc.com/contactor-ladn31

Product data sheet

| nRange | TeSys |
|--------------------------------|-------------------------|
| | TeSys Deca |
| Product name | TeSys Deca |
| Product or Component Type | Auxiliary contact block |
| Device short name | LADN |
| Range compatibility | TeSys D CAD |
| | TeSys D LC1D |
| | TeSys F LC1F |
| | TeSys F CR1F |
| | TeSys Deca CAD |
| | TeSys Deca LC1D |
| mounting location | Front |
| Pole contact composition | 3 NO + 1 NC |
| Contacts operation | Instantaneous |
| [Ue] rated operational voltage | 690 V AC 25400 Hz |
| [le] rated operational current | 6 A at 120 V AC-15 |
| | 1.04 A at 690 V AC-15 |
| | 0.55 A at 125 V DC-13 |
| | 0.1 A at 600 V DC-13 |
| [Ui] rated insulation voltage | 690 V IEC 60947-5-1 |

| | 600 V UL |
|---|--------------------------|
| | 600 V CSA |
| [Ith] conventional free air thermal current | 10 A (at 140 °F (60 °C)) |
| Standards | EN/IEC 60947-5-1 |
| | UL 60947-5-1 |
| | CSA C22.2 No 60947-5-1 |
| | GB/T 14048.5 |
| Product Certifications | СВ |
| | UL |
| | CSA |
| | ссс |
| | EAC |
| | UKCA |

| ComplementaryIrms rated mak | ylrms rated making capacity | 140 A AC conforming to IEC 60947-5-1 250 A DC conforming to IEC 60947-5-1 |
|-----------------------------|-------------------------------|--|
| | Permissible short-time rating | 100 A 140 °F (60 °C) 1 s |
| | | 120 A 140 °F (60 °C) 500 ms |
| | | 140 A 140 °F (60 °C) 100 ms |
| | Protection type | GG fuse 10 A |
| | Mechanical durability | 30 Mcycles |
| Minimu Non-ov Insulat | Minimum switching current | 5 mA |
| | Minimum switching voltage | 17 V |
| | Non-overlap time | 1.5 ms on de-energisation no overlap between NC and contact |
| | | 1.5 ms on energisation no overlap between NC and NO |
| | Insulation resistance | > 10 MOhm |
| | Connections - terminals | Screw clamp terminals 1 0.0020.006 in ² (14 mm ²)fl with cable end |
| | | |

| | screw clamp terminals 1 0.0020.006 in ² (14 mm ²)fle |
|-------------------|---|
| | without cable end |
| | screw clamp terminals 2 0.0020.004 in ² (12.5 mm ²) |
| | with cable end |
| | screw clamp terminals 2 0.0020.006 in ² (14 mm ²)fle |
| | without cable end |
| | screw clamp terminals 1 0.0020.006 in ² (14 mm ²)rig |
| | without cable end |
| | screw clamp terminals 2 0.0020.006 in ² (14 mm ²)rig |
| | without cable end |
| Tightening torque | 15.05 lbf.in (1.7 N.m) flat Ø 6 mm |
| | 15.05 lbf.in (1.7 N.m) Philips No 2 |
| | 15.05 lbf.in (1.7 N.m) pozidriv No 2 |
| Height | 1.9 in (48 mm) |
| Width | 1.7 in (44 mm) |
| Depth | 1.7 in (42 mm) |
| Net Weight | 0.11 lb(US) (0.05 kg) |
| color | Dark grey |

