



## spring return contact block XENG1191

URL:https://www.sxplc.com/spring-return-contact-block-xeng1191

## **Product data sheet**

Range of product	Harmony XAC
product or component type	Contact block
Component name	XENG
Electrical circuit type	Control circuit
Contact block application	2-speed
Contact block type	Single
Type of operator	Spring return
Product compatibility	XACA
	XACA9head
Contacts type and composition	1 NC + 2 NO
Mounting of block	Front mounting
Contact operation	Slow-break
	Staggered

	·	Connections - terminals	Screw clamp terminals, $1 \times 0.51 \times 2.5 \text{ mm}^2$ without ca
			Screw clamp terminals, $1 \times 0.52 \times 1.5 \text{ mm}^2$ with cable
		Mechanical durability	1000000 cycles
		Contact code designation	A600 AC-15, Ue = 240 V, Ie = 3 A conforming to IEC 60

1/3

	appendix A
	A600 AC-15, Ue = 600 V, Ie = 1.2 A conforming to IEC
	60947-5-1 appendix A
	Q600 DC-13, Ue = 250 V, Ie = 0.27 A conforming to IEC
	60947-5-1 appendix A
	Q600 DC-13, Ue = 600 V, Ie = 0.1 A conforming to IEC
	60947-5-1 appendix A
[Ithe] conventional enclosed thermal	10 A
current	
[Ui] rated insulation voltage	600 V (pollution degree 3) conforming to IEC 60947-1
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947-1
Maximum resistance across terminals	25 MOhm
Operating force	18 N
Short-circuit protection	10 A fuse protection by cartridge fuse type gG
Rated operational power in W	40 W DC-13 for 1000000 cycles, operating rate <60 cyc
	120 V, load factor = 0.5 (inductive load) conforming to
	60947-5-1 appendix C
	48 W DC-13 for 1000000 cycles, operating rate <60 cyc
	48 V, load factor = 0.5 (inductive load) conforming to IE
	60947-5-1 appendix C
	65 W DC-13 for 1000000 cycles, operating rate <60 cyc
	24 V, load factor = 0.5 (inductive load) conforming to IB
	60947-5-1 appendix C
Terminals description ISO n°1	(21-22)NC
	(33-34)NO_CL
	(13-14)NO
net weight	0.04 kg

2/3

