



PUSH BUTTON XB2BA31

URL: <https://www.sxplc.com/push-button-xb2ba31>

Product data sheet

Key messages

The product range is Easy Harmony XB2

Product Type button

Equipment IntroductionProduct (Non-Parts)

The product is nicknamed XB2

Frame material: nickel-plated metal

Mounting diameter 22.5 mm

Each item is sold separately in quantity1

Controlling head type standard

Supplemental information

Retaining ring material Zamak

ISO n°1 terminal (13-14) NO

Class I overvoltage according to IEC 60536

Position of operation: Any position

The operating head or lens color is green

Scope of application ZB2.. C

Equipment mounting holes - Diameter: 22.5 mm

Mounting hole spacing $\geq 30 \times 40$ mm (1...6 mm thick panels) Zamak zinc-based die-cast alloy -
Thickness: 1... 6 mm

Fixed mode set screw head recommended torque: 0.8 N.m

Fixing Screw Head Recommended torque: 1.0 N.m

The identity is not marked

The head of the signal unit is rounded

Operating head type spring return

Joystick profile green flat head, unmarked

Contact Type 1 NO

The contact action is slow to break

Standard contacts are used for contact wires

Force to open none

Operational propagation 2.88 mm (NO changes electrical state)

5.0 mm (total stroke)

Mechanical life 3000000 times

