



Shut-off valve, HE-2-QS-8

URL: <https://www.sxplc.com/shut-off-valve-he-2-qs-8>

Product data sheet

- | | |
|--|---|
| • Valve function | 2/2 double solenoid |
| • Pneumatic connection, port 1 | QS-8 |
| • Pneumatic connection, port 2 | QS-8 |
| • Type of actuation | Manual |
| • Type of mounting | Either: Direct mounting via through-hole In-line installation |
| • Standard nominal flow rate (standardised to DIN 1343) | 415.8 l/min |
| • Nominal size | 3.5 mm |
| • Operating pressure | 0.095 MPa ... 1 MPa |
| • Operating pressure | 0.95 bar ... 10 bar |
| • Ambient temperature | 0 °C ... 60 °C |
| • Material housing | PBT-reinforced |
| • Operating medium | Compressed air to ISO 8573-1:2010 [7:-:-] |
| • Sealing principle | Soft |

- **Mounting position** optional
- **Design** Piston gate valve
- **Type of piloting** Direct
- **Flow direction** Reversible
- **Symbol** 00997328
- **Note on operating and pilot medium** Lubricated operation possible
(in which case lubricated operation will always be required)
- **Corrosion resistance class** **CRC2** - Moderate corrosion stress
- **LABS (PWIS) conformity** VDMA24364-B1/B2-L
- **Cleanroom class** Class 4 according to ISO 14644-1
- **Media temperature** 0 °C ... 60 °C
- **Product weight** 26 g
- **Note on materials** RoHS-compliant
- **Material seals** NBR

