



## **CIRCUIT BREAKER 3RV2031-4WA10**

URL:https://www.sxplc.com/circuit-breaker-3rv2031-4wa10

## **Product data sheet**

mounting position	any
fastening method	screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 60715
height	140 mm
width	55 mm
depth	149 mm
required spacing	
<ul> <li>with side-by-side mounting at the side</li> </ul>	0 mm
<ul> <li>for grounded parts at 400 V</li> </ul>	
- downwards	50 mm
— upwards	50 mm
— at the side	10 mm
<ul> <li>for live parts at 400 V</li> </ul>	
- downwards	50 mm
— upwards	50 mm
— at the side	10 mm
<ul> <li>for grounded parts at 500 V</li> </ul>	
- downwards	50 mm
— upwards	50 mm
— at the side	10 mm
<ul> <li>for live parts at 500 V</li> </ul>	
- downwards	50 mm
— upwards	50 mm
— at the side	10 mm
<ul> <li>for grounded parts at 690 V</li> </ul>	
- downwards	50 mm
— upwards	50 mm
— at the side	10 mm
<ul> <li>for live parts at 690 V</li> </ul>	
- downwards	50 mm
— upwards	50 mm
— at the side	10 mm

