



## Foot-Pump HP227FP

URL: <https://www.sxplc.com/foot-pump-hp227fp>

### Product data sheet

The HP227FPC manually operated foot pump is supplied complete with a 4 inch diameter pressure gauge, gauge mounting block and 10 feet length hydraulic hose with CM1 quick connect male coupler. Ideally suited for use with CH series crimper heads and all other 10000 psi maximum working pressure, hydraulic tools that require a remote pump operation, the HP227FPC has a superb two speed low pressure displacement (0.79 inch<sup>3</sup> per stroke) with automatic changeover to high pressure displacement (0.14 inch<sup>3</sup> per stroke) up to 10000 psi. Supplied with a pre-filled oil reservoir offering a usable oil capacity of 140.35 inch<sup>3</sup>, the HP227FPC is supplied ready for immediate use.

The HP227FP pump incorporates the same specification and features of the HP227FPC pump however is supplied without the pressure gauge, gauge mounting block and 10 feet hose assembly.

Model Number	Valve Type	Usable Oil Cap. inch <sup>3</sup>	Displacement Per Stroke inch <sup>3</sup>		Handle Effort lbs	Weight lbs		Dimen A
			1st stage	2nd stage				
HP227FP	2-way	140.35	0.79	0.14	86	27.6		2

