

URL:https://www.sxplc.com/sewage-pump-mc-30-50

Product data sheet

Features

- MC series pumps, made from heavy gauge cast iron offering exceptional sturdiness, abrasion resistance and durability.
- Equipped with a DOUBLE-CHANNEL impeller and are capable of pumping liquids containing short fi bred suspended solids.
- Ideal for pumping sewage, waste water, water mixed with mud, groundwater and surface water in locations such as apartment blocks, public buildings, factories, tower garages, underground car parks and cleaning areas, etc.
- Pumped liquid: drainage dark water
- Passage of solids 50mm

Application limits

- 10 m maximum immersion depth
- Maximum liquid temperature +40°C
- Solids passage:
 - (a) up to Ø 50 mm for MC 15-20-30-40/50
 - (b) up to Ø 70 mm for MC 30-40/70
- Minimum immersion depth for continuous service:
 - (a) 380 mm for MC 15-20-30-40/50
 - (b) 430 mm for MC 30-40/70

Specifications

2½"	
	21/2"

Power	2200 W / Three phase
Flow Rate	100 ~ 1100 L/min
Head	22~ 2 meters
Immersion Limit	Max. 10 meters
Liquid Temperature	Max. +40°C
Environment Temperature	Max. +40°C
Dimensions Ø x H	345mm x 517mm
Weight	39 kg

Power cable 10m

