



## front-side auxiliary switch, 1 NO contact, spring-type terminal, for contactors 3RT1 3RH1921-2CA10

URL:https://www.sxplc.com/front-side-auxiliary-switch-1-nocontact-spring-type-terminal-for-contactors-3rt1-3rh1921-2ca10

**Product data sheet** 

insulation voltage with degree of pollution 3 at AC rated value	690 V
surge voltage resistance rated value	6 kV
protection class IP on the front	IP20
mechanical service life (operating cycles) typical	10 000 000
electrical endurance (operating cycles) at AC-15 at 230 V typical	200 000
Substance Prohibitance (Date)	07/01/2006
number of NC contacts for auxiliary contacts	
<ul> <li>instantaneous contact</li> </ul>	0
number of NO contacts for auxiliary contacts	
<ul> <li>instantaneous contact</li> </ul>	1
number of CO contacts of auxiliary contacts instantaneous contact	0
operational current at AC-15 at 690 V rated value	1 A
operational current of auxiliary contacts at AC-12	
• at 24 V	10 A
• at 230 V	10 A
operational current of auxiliary contacts at AC-14	
• at 125 V	6 A
• at 250 V	6 A
operational current of auxiliary contacts at AC-12 maximum	10 A
operational current of auxiliary contacts at AC-15	
• at 24 V	6 A
• at 230 V	6 A
• at 400 V	3 A
operational current of auxiliary contacts at DC-12	
• at 24 V	10 A
• at 110 V	3 A
• at 220 V	1 A