



contactor 3P A9-30-10 220-230V

50Hz 230-240V - 1SBL141001R8010

URL:<https://www.sxplc.com/contactor-3p->

[a9-30-10-220-230v-50hz-230-240v-1sbl141001r8010](https://www.sxplc.com/contactor-3p-a9-30-10-220-230v-50hz-230-240v-1sbl141001r8010)

Product data sheet

Rated Control Circuit Voltage (Uc)

50 Hz 220-230V; 60 Hz 230-240V

Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1

8 x Ie AC-3

Rated Operational Power AC-3 (Pe)

(220 / 230 / 240 V) 2.2 KWT, (380 / 400 V) 4 KWT, (415 V) 4 KWT, (440 V) 4 KWT, (500 V) 5.5 KWT, (690 V) 5.5 KWT

Rated Operational Current DC-13 (Ie)

(125 V) 1.1 / 138 ampere, (24 V) 6 / 144 ampere, (250 V) 0.55 / 138 ampere, (48 V) 2.8 / 134 ampere,

(72 V) 2 / 144 ampere

Rated Operational Current AC-3 (I_e)

(220 / 230 / 240 V) 55 °C 9 ampere, (380 / 400 V) 55 °C 9 ampere, (415 V) 55 °C 9 ampere, (440 V) 55 °C 9 ampere, (500 V) 55 °C 9 ampere, (690 V) 55 °C 7 ampere

Rated Operational Current AC-15 (I_e)

(220 / 240 V) 4 ampere, (24 / 127 V) 6 ampere, (380 / 440 V) 3 ampere, (500 V) 2 ampere, (690 V) 2 ampere

Rated Operational Current AC-1 (I_e)

(690 V) 40 °C 25 ampere, (690 V) 55 °C 22 ampere, (690 V) 70 °C 18 ampere

Rated Making Capacity AC-3 acc. to IEC 60947-4-1

10 x I_e AC-3

Rated Breaking Capacity acc. to IEC 60947-5-1

10 x I_e AC-15

Rated Frequency Limits

25 ... 400 hertz

Rated Frequency (f)

Supply Circuit 50 60 hertz

Number of Aux Contacts NO

1

Package Width

78 millimetre

Package Length

76 millimetre

Package Height

47 millimetre

Package Gross Weight

0.34 kilogram

