



Air solenoid valve VUVG- L10-M52-MZT-M7-1P3

URL: <https://www.sxplc.com/air-solenoid-valve-vuvg-l10-m52-mzt-m7-1p3>

Product data sheet

- | | |
|-------------------------------------|---|
| • Valve function | 5/2, monostable |
| • Actuation type | Electrical |
| • Valve size | 10 mm |
| • Standard nominal flow rate | 320 l/min |
| • Pneumatic working port | M7 |
| • Operating voltage | 24V DC |
| • Operating pressure | 0.09 MPa ... 0.8 MPa |
| • Operating pressure | 0.9 bar ... 8 bar |
| • Structural design | Piston gate valve |
| • Reset method | Mechanical spring |
| • Certification | RCM compliance mark c UL us - Recognized (OL) |
| • Degree of protection | IP40 IP65 With plug socket |
| • Nominal width | 2.8 mm |
| • Exhaust air function | With flow control option |

- **Sealing principle**Soft
- **Mounting position**Any
- **Manual override**Detenting Non-detenting Covered
- **Type of control**Pilot-controlled
- **Pilot air supply port**External
- **Symbol**00991190
- **Lap**Overlap
- **Pilot pressure MPa**0.3 MPa ... 0.8 MPa
- **Pilot pressure**3 bar ... 8 bar
- **Suitability for vacuum**yes
- **Switching time off**24 ms
- **On switching time**8 ms
- **Duty cycle**100%
- **Max. positive test pulse with 0 signal**700 μ s
- **Max. negative test pulse on 1 signal**900 μ s
- **Coil characteristics**24 V DC: 1.0 W 24 V DC: low-current phase 0.3 W, high-current phase 1.0 W
- **Permissible voltage fluctuations**+/- 10 %
- **Operating medium**Compressed air as per ISO 8573-1:2010 [7:4:4]
- **Information on operating and pilot media**Operation with oil lubrication possible (required for further use)
- **Vibration resistance**Transport application test with severity level 2 as per FN 942017-4 and EN 60068-2-6

- **Restricted ambient and media temperature**-5 - 50 °C Without holding power reduction
- **Shock resistance**Shock test with severity level 2 as per FN 942017-5 and EN 60068-2-27
- **Corrosion resistance class (CRC)**2 - Moderate corrosion stress
- **LABS (PWIS) conformity**VDMA24364-B1/B2-L
- **Temperature of medium**-5 °C ... 60 °C
- **Pilot medium**Compressed air as per ISO 8573-1:2010 [7:4:4]
- **Ambient temperature**-5 °C ... 60 °C
- **Product weight**44 g
- **Electrical connection**Via electrical sub-base
- **Type of mounting**Optionally: On terminal strip With through-hole
- **Pilot air port 12/14**M3
- **Pneumatic connection 1**M7
- **Pneumatic connection 2**M7
- **Pneumatic connection 4**M7
- **Pneumatic connection 5**M7
- **Note on materials**RoHS-compliant
- **Seals material**HNBR NBR
- **Housing material**Wrought aluminum alloy

