




Photoelectric proximity sensor

WT160-F480

URL:<https://www.sxplc.com/photoelectric-proximity-sensor-wt160-f480>

Product data sheet

| | |
|---------------------|------------------------------------------------------------------------------------|
| Dimensional drawing |  |
| Width | 45 mm |
| Height | 126.1 mm |
| Depth | 74 mm |
| Note on dimensions | The depth applies when a TH 35-7.5 DIN rail is used (in accordance with EN 60715). |

Notes

| | |
|-------------------------|---------------------------------------------------------------------------|
| Note on application | Only for industrial use |
| Utilization restriction | |
| EMC note | EMC: class A product, see manufacturer's declaration in the download area |

Interfaces

PROFINET

| | |
|-------------------------------|-----------------------------------|
| Number of interfaces | 2 |
| Connection method | RJ45 jack |
| Note on the connection method | Auto negotiation and autocrossing |
| Transmission speed | 100 Mbps (full duplex) |
| Transmission physics | Ethernet in RJ45 twisted pair |

Axioline F local bus

| | |
|----------------------|-----------------|
| Number of interfaces | 1 |
| Connection method | Bus base module |
| Transmission speed | 100 Mbps |

Service

| | |
|----------------------|------------|
| Number of interfaces | 1 |
| Connection method | USB type C |

