

Contactor LA1KN22

URL:<https://www.sxplc.com/contactor-la1kn22>

Product data sheet

Complementary	Irms rated making capacity	110 A at <= 690 V AC conforming to IEC
	Permissible short-time rating	80 A 1 s 60 A 500 ms 110 A 100 ms
	Associated fuse rating	10 A gG at <= 690 V conforming to IEC
	Minimum switching current	5 mA
	Minimum switching voltage	17 V
	Non overlap distance	0.02 in (0.5 mm)
	Insulation resistance	> 10 MOhm
	Connections - terminals	Screw clamp terminals 1 0.0005...0.002 in² (0.75...1.5 mm²)flexible with cable end screw clamp terminals 1 0.001...0.006 in² (0.75...1.5 mm²)without cable end screw clamp terminals 1 0.002...0.006 in² (1.5...2.5 mm²)without cable end screw clamp terminals 2 0.0005...0.002 in² (0.75...1.5 mm²)flexible with cable end screw clamp terminals 2 0.001...0.006 in² (0.75...1.5 mm²)without cable end screw clamp terminals 2 0.002...0.006 in² (1.5...2.5 mm²)without cable end

		11.5 lbf.in (1.3 N.m) pozidriv No 2
	Tightening torque	11.5 lbf.in (1.3 N.m) Philips No 2
	Height	1.2 in (30 mm)
	Width	1.5 in (38 mm)
	Depth	1.4 in (35 mm)
	Net Weight	0.099 lb(US) (0.045 kg)

