Electropneumatic Positioner

4763-01200121000000.04

URL:https://www.sxplc.com/electropneumatic-positioner-4763-01200121000000-04

Product data sheet

Product number	4763 -	□	0	1	□	0	0	□	□	□	□	0
Intrinsically safe												
Without		0										
EEx ia IIC T6		1										
Ex ia FM/CSA		3										
Measuring spring												
1					1							
2					2							
3					3							
Pneumatic connections												
G ¼								1				
NPT ¼								3				
Electrical connections												
Pg 13.5 blue									1			
Pg 13.5 black									2			
½" F-NPT									3			
½" F-NPT metal bushing with pre-wired leads									4			
Plug connector Harting HAN 7 D									5			
Input signal												
[illegible]										1	1	
[illegible]										2	2	
[illegible]										2	3	
[illegible]										1	4	
[illegible]										1	5	

Product number	4765–	0	1	□	0	0	□	1
Measuring spring								
1				1				
2				2				
3				3				
Pneumatic connections								
G ¼							1	
NPT ¼							3	

Additional ordering text

Without/with pressure gauges
Pressure gauge casing of stainless steel, nickel-plated connection/ complete stainless steel

Specify when mounting on the control valve
Adjusted input signal ... ; air supply ... psi (bar)
Operating action: Increasing-increasing/increasing-decreasing
Tubing: copper-brass/stainless steel/
Nominal tube diameter ¼"/⅜" (6/10 mm)

Specify when attaching to valves with NAMUR yokes
Travel ... inches (mm)

Specify when attaching to valves with rod-type yokes
Travel ... inches (mm)
Rod diameter ... inches (mm)