

Thermal overload relay,LRD12

URL:<https://www.sxplc.com/thermal-overload-relay-lrd12>

Product data sheet

Thermal protection adjustment range	5.5...8 A
[Ui] rated insulation voltage	Power circuit 600 V CSA Power circuit 600 V UL Power circuit 690 V IEC 60947-4-1

Complementary	Network Frequency	0...400 Hz
	Mounting support	Plate, with specific accessories Rail, with specific accessories Under contactor
	Tripping threshold	1.14 +/- 0.06 Ir IEC 60947-4-1
	Auxiliary contact composition	1 NO + 1 NC
	[Ith] conventional free air thermal current	5 A signalling circuit
	Permissible current	1.5 A 240 V AC-15 signalling circuit 0.1 A 250 V DC-13 signalling circuit
	[Ue] rated operational voltage	690 V AC 0...400 Hz power circuit IEC 60947-4-1
	Associated fuse rating	4 A gG for signalling circuit 4 A BS for signalling circuit
	[Uimp] rated impulse withstand voltage	6 kV
	Phase failure sensitivity	Tripping current 130 % of Ir on two phase, the last one
	Control type	Red push-button stop

		Blue push-button reset
	Temperature compensation	-4...140 °F (-20...60 °C)

