



Floatless Level Switch,61F-G3

URL:https://www.sxplc.com/floatless-level-switch-61f-g3

Product data sheet

Type High/Low Level Voltage - Supply 110/220VAC Sensitivity 0 ~ 4kOhm Features Alarm High/Low - Contact Distance - Control To Sensor (Max) 1km Output Type Relay (3) Contact Form SPDT (2 Form C) Contact Rating @ Voltage 5A @ 220VAC Mounting Type Chassis Mount Termination Style Screw Terminal Operating Temperature -10°C ~ 55°C Weight 2.1 lbs (952.5 g) Base Product Number		
Sensitivity O ~ 4kOhm Features Alarm High/Low - Contact Distance - Control To Sensor (Max) 1km Output Type Relay (3) Contact Form SPDT (2 Form C) Contact Rating @ Voltage 5A @ 220VAC Mounting Type Chassis Mount Termination Style Screw Terminal Operating Temperature -10°C ~ 55°C Weight 2.1 lbs (952.5 g)	Турс	e High/Low Level
Features Alarm High/Low - Contact Distance - Control To Sensor (Max) 1km Output Type Relay (3) Contact Form SPDT (2 Form C) Contact Rating @ Voltage 5A @ 220VAC Mounting Type Chassis Mount Termination Style Screw Terminal Operating Temperature -10°C ~ 55°C Weight 2.1 lbs (952.5 g)	Voltage - Supply	110/220VAC
Alarm High/Low - Contact Distance - Control To Sensor (Max) 1km Output Type Relay (3) Contact Form SPDT (2 Form C) Contact Rating @ Voltage 5A @ 220VAC Mounting Type Chassis Mount Termination Style Screw Terminal Operating Temperature -10°C ~ 55°C Weight 2.1 lbs (952.5 g)	Sensitivity	0 ~ 4kOhm
Output Type Relay (3) Contact Form SPDT (2 Form C) Contact Rating @ Voltage 5A @ 220VAC Mounting Type Chassis Mount Termination Style Screw Terminal Operating Temperature -10°C ~ 55°C Weight 2.1 lbs (952.5 g)	Feature	
Contact Form SPDT (2 Form C) Contact Rating @ Voltage 5A @ 220VAC Mounting Type Chassis Mount Termination Style Screw Terminal Operating Temperature -10°C ~ 55°C Weight 2.1 lbs (952.5 g)	Distance - Control To Sensor (Max	
Contact Rating @ Voltage 5A @ 220VAC Mounting Type Chassis Mount Termination Style Screw Terminal Operating Temperature -10°C ~ 55°C Weight 2.1 lbs (952.5 g)	Output Type	Relay (3)
Mounting Type Chassis Mount Termination Style Screw Terminal Operating Temperature -10°C ~ 55°C Weight 2.1 lbs (952.5 g)	Contact Forn	
Termination Style Screw Terminal Operating Temperature -10°C ~ 55°C Weight 2.1 lbs (952.5 g)	Contact Rating @ Voltage	5A @ 220VAC
Operating Temperature -10°C ~ 55°C Weight 2.1 lbs (952.5 g)	Mounting Type	e Chassis Mount
-10°C ~ 55°C Weight 2.1 lbs (952.5 g)	Termination Style	Screw Terminal
2.1 lbs (952.5 g)	Operating Temperature	-10°C ~ 55°C
Base Product Number 61F	Weigh	2.1 lbs (952.5 g)
	Base Product Numbe	<u>61F</u>

1/2

