



## Plug socket MSSD-F-S-M16

URL: <https://www.sxplc.com/plug-socket-mssd-f-s-m16>

### Product data sheet

- |   |   |
|---|---|
| • <b>Frequency of connection</b>                              | 50  |
| • <b>Cable outlet</b>   | Angled  |
| • <b>Note on cable outlet</b>                                 | 180° rotatable                                  |
| • <b>Product weight</b>                                       | 35 g  |
| • <b>Electrical connection 1, design</b>                      | Angular   |
| • <b>Electrical connection 1, connection type</b>             | Socket  |
| • <b>Electrical connection 1, connector system</b>            | Plug pattern type B to industry standard, 11 mm |
| • <b>Electrical connection 1, number of connections/cores</b> | 3   |
| • <b>Electrical connection 1, type of mounting</b>            | On solenoid valve via M3 central screw          |
| • <b>Electrical connection 1, connection pattern</b>          | 00995619  |
| • <b>Electrical connection 2, connector system</b>            | Screw terminal                                  |
| • <b>Operational voltage range DC</b>                         | 0 V ... 250 V                                   |
| • <b>Operational voltage range AC</b>                         | 0 V ... 250 V                                   |

- **Current rating at 40° C** 6 A
- **Immunity to surge** 2 kV
- **Protective conductor connection** Available
- **Cable fitting** M16x1.5
- **Cable diameter** 6 mm ... 8 mm
- **Nominal cross section conductor**  $\leq 0.75 \text{ mm}^2$
- **Degree of protection** IP65
- **Note on degree of protection** In assembled state
- **Ambient temperature** -20 °C ... 115 °C
- **LABS (PWIS) conformity** VDMA24364-B2-L
- **Note on materials** RoHS-compliant
- **Pollution degree** 3
- **Corrosion resistance class** CRC1 - Low corrosion stress
- **Material housing** PA-reinforced
- **Housing colour** Black
- **Material seals** HNBR

