



## Contactor 3RT6023-1AN20

URL: <https://www.sxplc.com/contactor-3rt6023-1an20>

### Product data sheet

Contactor Construction Size S0

Product Extension Auxiliary Switch Yes

Power Loss [W] at Current Measurement Value

- At AC 0.4 W per electrode in thermal operation

- No load current share Typical 1.97 W

Lost power calculation type Electrode-related Orthogonal

Insulation voltage Measured value 690 V

Degree of contamination 3

Insulation voltage Measured value 690 V Pollution level 3 Power against shock voltage Measured value 6 kV

Maximum permissible voltage for safe isolation Between coil and main contacts in accordance with EN 60947-1

60947-1

400 V

Shock resistance ● At square wave impact 7,5g / 5g at AC

7,5g / 5 ms, 4,7g / 10 ms at ● AC

Shock resistance at sinusoidal shock

11,8g/5 ms, 7,4g/10 ms at AC

Mechanical user life (changeover cycle)

● Typical 10,000,000 for contactors

Typical 10,000,000 for contactors with auxiliary switching block

Installation altitude Altitude above water Maximum 2 000 m

Ambient temperature

-25 ... +60 °C during operation +60 °C

During storage -55 ... +80 °C +80 °C

Number of Poles Used for Main Circuit 3

Number of Normally Open Contacts Used for Main Contacts 3

Number of Normally Closed Contacts Used for Main Contacts 0

Operating Voltage

- Measured value at AC-3 Maximum value 690 V

- Measured value at AC-3e Maximum 690 V

Working current

- Up to 690 V at AC-1

- Measured value at 40 °C ambient temperature 40 A

- Measured value at 60 °C ambient temperature 35 A

- At AC-3

- 9 A measured at 400 V

- 9 A measured value at 690 V

Measured value at 690 V 9 A at 400 V ● At AC-3e

- Measured value at 400 V 9 A at 690 V

- Measured value at 690 V 9 A

Connectable wire cross-section in the main circuit ● Maximum permissible value at 60 °C

● Maximum permissible value 10 mm<sup>2</sup> at 60 °C

● Maximum permissible value 10 mm<sup>2</sup> at 40 °C

Operating current Approx. 200000 operating cycles AC-4

● Measured value at 400 V 4.1 A

● 3.3 A measured value at 690 V

Rated power

● At AC-1

- Measured value at 230 V 13.3 kW

- Measured value at 60 °C at 230 V 13.3 kW

- Measured value at 60 °C at 400 V 23 kW

- Measured value at 60 °C at 690 V 40 kW

Measured value at 60 °C at 690 V

- ● Measured value at 230 V 2.2 kW

- Measured value at 400 V 4 kW

- Measured value at 690 V 7.5 kW

Measured value at 690 V 7.5 kW at AC-3e

- AC-3e Measured value at 230 V 2.2 kW Measured value at 400 V 4 kW

- Measured value at 400 V 4 kW Measured value at 690 V 7.5 kW

- Measured value at 690 V 7.5 kW

Measured value at 690 V 7.5 kW Rated power Approx. 200,000 operating cycles AC-4

● Measured value at 400 V 2 kW

Measured value at 400 V 2 kW Measured value at 690 V 2.5 kW

No-load frequency

5,000 1/h at ● AC

Switching frequency

Maximum 1 000 1/h at AC-1 ● Maximum 1 000 1/h at AC-3

Maximum value at AC-1 1 000 1/h ● Maximum value at AC-3 1 000 1/h

Maximum 1 000 1/h at AC-3e ● Maximum 1 000 1/h at AC-4

Maximum value 300 1/h for AC-4 ● Maximum value 300 1/h for AC-4

Voltage type AC at control feed voltage

When controlling the feed voltage AC

- Measured value at 50 Hz 220 V

- Measured value at 60 Hz 220 V

Measured value of the control feed voltage for the working area elements AC for solenoid coils

- At 50 Hz 0.8 ... 0.8 ... 1.1 at 50 Hz

0.85 at 60 Hz ... 1.1 at 60 Hz 1.1

Starting apparent power AC with solenoid coil

68 VA at 50 Hz

67 VA at 60 Hz

Induced power factor Starting power for coil

- 0.72 at 50 Hz

0.74 at 60 Hz

Stopping apparent power AC of solenoid coil

- 7.9 VA at 50 Hz

- 6.5 VA at 60 Hz

Induced power factor Stopping power for coil

- 0.25 at 50 Hz

0.28 at 60 Hz

Number of Normally Closed Contacts Used for Auxiliary Contacts 1 for No Delayed Changeover

Number of normally open contacts 1 for auxiliary contacts without delayed changeover

Maximum value 10 A at operating current AC-12

Maximum value at operating current AC-12 10 A at operating current AC-15

- 10 A measured value at 230 V

- 3 A measured value at 400 V

- Measured value 1 A at 690 V Operating current DC-12

Measured value 1 A at 690 V Working current DC-12

Measured value at 24 V 6 A Measured value at 110 V

- Measured value at 110 V 3 A

Measured value at 220 V 1 A Working current DC-13

Measured value 1 A at 220 V Working current DC-13

Measured value at 24 V 6 A ● Measured value at 110 V

Measured value 6 A at 24 V ● Measured value 1 A at 110 V

● Measured value at 220 V 0.3 A

Contact reliability 1 misconnection per 100 million transitions of the auxiliary contact (17 V, 1 mA)

Mounting position Rotatable +/-180° for vertical mounting, tiltable +/- 22.5° for vertical mounting.

Type of fastening Screw and snap fastening on 35 mm mounting rail according to DIN EN 50022

Side-by-side assembly Yes

Height 85 mm

Width 45 mm

Depth 97 mm

Spacing to be observed 0 mm lateral ground for single row mounting

