



## Fan unit,SK 3244.100

URL:<https://www.sxplc.com/fan-unit-sk-3244-100>

### Product data sheet

SK 3244.100
Version
wall-mounted
Product description
Filter fans with diagonal fan technology are more pressure-resistant and produce more constant air performance. The diagonal outflow direction ensures a more uniform heat dissipation from the enclosure.
Color
RAL 7035
Supply includes
Complete unit ready to install, including fleece filter mat
Fan
Diagonal, 1~ capacitor motor
Unimpeded air flow (with fleece filter)
At 50 Hz: 700 m³/h At 60 Hz: 770 m³/h ( At 50 Hz: 412 cfm At 60 Hz: 453.2 cfm )
Unimpeded air flow (with folded filter)
At 50 Hz: 855 m³/h At 60 Hz: 905 m³/h

( At 50 Hz: 503.23 cfm  
At 60 Hz: 532.66 cfm )

Air throughput with outlet filter incl. fleece filter mat (quantity x order number)

1 x 3243200: 485/520 m³/h  
2 x 3243200: 570/630 m³/h

Rated operating voltage

230 V, 1~, 50 Hz/60 Hz

Rated power  $P_{el}$

At 50 Hz: 95 W  
At 60 Hz: 135 W

Rated current max.

At 50 Hz: 0.43 A  
At 60 Hz: 0.6 A

Dimensions

Width: 323 mm  
Height: 323 mm  
( Width: 12.7 " )  
Height: 12.7 " )

