# Fan unit, SK 3244.100

URL:https://www.sxplc.com/fan-unit-sk-3244-100

## **Product data sheet**

SK 3244.100
version
- Wall-mounted
Froduct description Filter fans with diagonal fan technology are more pressure-resistant and produce
more constant air performance. The diagonal outflow direction ensures a more
uniform neat dissipation from the enclosure.
_olor
RAL 7035
Supply includes
Complete unit ready to install, including fleece filter mat
-an Diagonal I canacitar motor
Diagonal, 1~ capacitor motor
Unimpeded air flow (with fleece filter)  At 50 Hz: 700 m³/h
At 60 Hz: 770 m³/h
( At 50 Hz: 412 cfm At 60 Hz: 453.2 cfm )
At 00 Hz. 455.2 Citil )
Unimpeded air flow (with folded filter)  At 50 Hz: 855 m³/h
At 60 Hz: 905 m³/h
( At 50 Hz: 503.23 cfm At 60 Hz: 532.66 cfm )
AC OUTIL. JJZ.00 CIIII )

1/2

### Air throughput with outlet filter incl. fleece filter mat (quantity x order number)

1 X 3243200: 485/520 m³/n 2 X 3243200: 570/630 m³/n

#### Kated<u>operating voltage</u>

230 V, 1~, 50 HZ/60 HZ

#### Kated<u>power Pel</u>

At 50 Hz: 95 W At 60 Hz: 135 W

#### Kated<u>current max.</u>

At 50 Hz: 0.43 A At 60 Hz: 0.6 A

#### Dimensions

Width: 323 mm Height: 323 mm ( Width: 12.7 "

Height: 12.7 )

